



## PROSPEC® Composite

### Product Information

#### Applications

- Over substandard walls between manufacturing plant and offices
- To line thin enclosures around machinery, air compressors or similar noise sources
- In engine compartments
- Under machinery hoods

PROSPEC Composite combines the benefits of both willtec® acoustical foam and the noise containment capabilities of vinyl barrier into one durable product consisting of :

- 1" thick layer of Hypalon®-coated willtec foam, to absorb noise.
- 1/8" thick noise barrier, to contain noise and reduce sound transmission.
- 1/4" thick willtec decoupler to provide air space between the barrier and the mounting surface for optimal noise containment. This decoupler helps to insulate the barrier from vibrations in the wall.

PROSPEC Composite is an attractive solution for absorbing and containing noise and vibrations in many different types of settings. The panels come standard with a convoluted surface and gray Hypalon facing for easy clean-up. Rugged Tedlar® facing is available to withstand harsher chemicals and cleaning. Aluminized Mylar® is also available for special applications.

#### Physical Data

Material	1" open-cell willtec bonded to 1/8" loaded vinyl barrier with 1/4" willtec decoupler layer
Surface Pattern	Sculpted – Hypalon-coated surface absorbs sound waves
Density	willtec foam 0.7 pounds per cubic foot
Tensile Strength	8 PSI
Flammability	Class 1 per ASTM E84
Flame Spread	Hypalon-coated Foam – 25
Smoke Density	Hypalon-coated Foam – 65

Frequencies Hz	ASTM E90-90 Transmission Loss	Frequencies Hz	ASTM C423-90a Sound Absorption Coefficients*
125	17	125	0.13
250	22	250	0.60
500	20	500	0.81
1000	32	1000	0.97
2000	31	2000	1.00
4000	43	4000	0.90
STC**	28	NRC	0.85

\*\*Estimated

\*Type B Mounting

2601 49th Avenue North  
Suite 400  
Minneapolis, MN 55430  
Toll-Free 1-800-662-0032  
sales@pinta-acoustic.com  
www.pinta-acoustic.com